

This product comes with a
2
Year Warranty



Shown with optional accessories

PROSCALE™

- Displays how much material is being removed per pass
- Displays zero when the desired thickness is reached
- Displays the actual thickness of the stock as it exits the sander
- Standard on 220Volt Series 50x2 drum sanders (Optional on all other models)

50 x 2 DRUM SANDER

- Continuous-duty 7-1/2HP motor, 208 - 230 Volt power, single or 3 phase
- SandSmart™ automatic control of the infinite-variable feed rate of the conveyor (0-15 ft./min.)
- Precisely dimension stock within .010" across width of sander
- Magnetic starter
- Multiple grit sanding in a single pass
- 50" wide, dual (x 2) drum sanding capacity
- Casters included, (wheel and swivel lock)
- Electric height adjustment, high speed and adjustable speed
- ProScale depth gauge (DRO) in sures proper dimensioning
- Precision-flattened steel conveyor bed reinforced with four steel cross sections for no "flex"
- Self-cooling drum with abrasive Take-up Fasteners, make changing abrasives quick and easy and keeps abrasives tight
- Sand stock as short as 3-1/2" as thin as 1/32" and as thick as 12"
- Cast stand zinc-plated steel bed, center less ground column tubes
- Minimum of 1800 CFM dust collection recommended
- Shipped assembled, some minimal assembly required
- Drum ball bearings are sealed and permanently lubricated

220 VOLT MODELS

- 750102** SUPERMAX 50x2 dual drum, 1 Ph
- 750302** SUPERMAX 50x2 dual drum, 3 Ph

OPTIONAL ACCESSORIES

- 59120** ABRASIVE CLEANING STICK
- 61-1010** 50" POLY CONVEYOR BELT
- 98-0070** RACK-N-ROLL (ABRASIVE STORAGE SHELF)
"PRE-MARKED" ABRASIVES- 24 TO 220 GRIT

Sanding Capacity	
Maximum Width (in):	50
Minimum Length (in):	3 1/2
Maximum Thickness (in):	12
Minimum Thickness (in):	1/32
Dimensions (H x W x D/in):	50 x 71 x 31
Drums:	Extruded aluminum
	5 x 50 (2)
Drum Speed:	1600 RPM
Dust Hood:	Hinged back steel with
	3- 4" vacuum ports
Height Adjustment (in):	Power and manual
	controls, 3/32 per turn;
	ProScale™ digital
	read-out and locking
	stop included
Ball Bearings (1")	4
Conveyor Motor :	SandSmart™ controlled
	220 in.-lb. torque, direct
	drive D.C. motor,
	Infinitely variable 0-15
	feet per minute
Drive Motor (TEFC):	7-1/2 HP, 1740 RPM;
	208-230V, 60HZ;
	continuous-duty.
Power Requirements:	1 Ph, 50 amp service
	3 Ph, 30 amp service
Shipping Weight (lbs):	820