



SUPERBRUSH 52 x 2 DOUBLE BRUSH

- 800 % faster than a 36" single head brush sander.
- Sample testing available & encouraged
- Bristle contact gauge (depth gauge) included, electronic & programmable
- Both brushes can be angled up to 15°
- Straight-line metal up to 60 ft/min.
- Independently adjustable brush heads, RPM, contact, rotation
- Graining or decorative finishing is a great application for a SuperBrush sander. This can be accomplished using a nylon or flatter style brush. The best brush choice will depend on desired appearance, condition of the material before brushing, type of material and plating or painting, if any.
- Light de-burring can be accomplished on many materials by utilizing an aggressive wire or nylon brush and can compliment the wide belt sanders as a second step to radius edges and remove secondary burrs left by belt sanders.
- Polishing & buffing metal is accomplished using either nylon or Scotch-Brite® heads. This is a great way to bring out the sheen of a surface or finish.
- A modified version of straight lining is accomplished using the brush sander and a nylon or flatter style brush. The brush will generate less heat and better conform to slight differences in thickness and the brush will have a much longer life than compared to abrasives on the wide belt.
- Cleaning and de-scaling can be done with nylon or flatter, depending on the degree of contamination removal and the base material.
- Scuff sanding and primer sanding (base coat sanding) are easily accomplished with either nylon or flatter style brushes. This is much faster and more consistent as compared to hand sanding or scuffing.
- Oxidation removal is accomplished with aggressive wire or nylon brushes, unless very deep when a wide belt is required.

Note: The SuperBrush 52 x 2 offers nylon, flatter and polishing (not wire) for even faster sanding.

220 VOLT MODEL

43552 SB Pro Series 36" Double Head Brush Sander -3 PH

AVAILABLE BRUSHES

NYLON/SILCON CARBIDE (TYPICAL GRIT 80,120,240)
FLADDER STYLE- SPECIFY GRIT (60-400)
SCOTCH-BRITE®
CUSTOM BRUSHES AVAILABLE

Sanding Capacity	
Maximum Width (in):	51
Minimum Length (in):	24
Maximum Thickness (in):	6 (varies with brush style)
Minimum Thickness (in):	1/8
Dimensions (L x W x H/in):	
SuperBrush 52 x 2	84 x 96 x 84
Brush (in):	11-12" diameter typical; typical bristle length 1-1/2 to 3"
Brush Speed:	Infinitely variable 160 to 640 RPM
Dust Hoods:	
SuperBrush 52 x 2	2 - 5" vacuum ports 1800 CFM. Min.
Height Adjustment (in):	1 HP motor Electronically controlled
Conveyor Motor :	2 HP Infinitely variable 12-60 feet per minute
Brush Motors (TEFC):	(2) - 2 HP 208-230V, 60HZ; continuous-duty.
Power Requirements:	3 Ph, 30 amp service
Shipping Weight (lbs):	
SuperBrush 52 x 2	7700