

**SUPERBRUSH PRO SERIES
DOUBLE HEAD BRUSH SANDERS**

- Now Available in 25", 37", 52", 62" and 74" widths!
- 800% faster than a single head brush sander.
- Straight-line metal up to 60 ft/min.
- Bristle contact gauge (depth gauge) included, electronic & programmable.
- Both brushes can be angled up to 15°.
- Independently adjustable brush heads, RPM, contact, rotation.
- Graining or decorative finishing is a great application for a SuperBrush sander. This can be accomplished using a nylon or flatter style brush. The best brush choice will depend on desired appearance, condition of the material before brushing, type of material and plating or painting, if any.
- Light de-burring can be accomplished on many materials by utilizing an aggressive wire or nylon brush and can compliment the wide belt sanders as a second step to radius edges and remove secondary burrs left by belt sanders.
- Polishing & buffing metal is accomplished using either nylon or Scotch-Brite® heads. This is a great way to bring out the sheen of a surface or finish.
- A modified version of straight lining is accomplished using the brush sander and a nylon or flatter style brush. The brush will generate less heat and better conform to slight differences in thickness and the brush will have a much longer life than compared to abrasives on the wide belt.
- Cleaning and de-scaling can be done with nylon or flatter, depending on the degree of contamination removal and the base material.
- Scuff sanding and primer sanding (base coat sanding) are easily accomplished with either nylon or flatter style brushes. This is much faster and more consistent as compared to hand sanding or scuffing.
- Oxidation removal is accomplished with aggressive wire or nylon brushes, unless very deep when a wide belt is required.



Sanding Capacity	
Maximum Width (in):	Varies by machine
Minimum Length (in):	Varies by machine
Maximum Thickness (in):	6 (varies with brush style)
Minimum Thickness (in):	1/8
Dimensions (L x W x H/in):	Varies by machine
Brush (in)	11-12" diameter typical; Typical bristle length 1-1/2 to 3"
Brush Speed	Infinitely variable 160 to 640 RPM
Dust Hoods	2-5" vacuum ports 1800 CFM Minimum
Height Adjustment (in):	1 HP motor Electronically controlled
Conveyor Motor:	2 HP motor Infinitely variable 12-60 ft/min
Brush Motors (TEFC):	Two-2 HP motors 208-230V, 60HZ continuous-duty
Power Requirements:	3 Ph, 30 amp service
Shipping Weight (lbs):	
SB Pro Series 25"	6700
SB Pro Series 37"	7716
SB Pro Series 52"	9716
SB Pro Series 62"	11500
SB Pro Series 74"	12600

220 VOLT MODEL

- 73525 SB Pro Series 25" Double Head Brush Sander 220V- 3PH
- 73537 SB Pro Series 37" Double Head Brush Sander 220V- 3PH
- 73552 SB Pro Series 52" Double Head Brush Sander 220V- 3PH
- 73562 SB Pro Series 62" Double Head Brush Sander 220V- 3PH
- 73574 SB Pro Series 74" Double Head Brush Sander 220V- 3PH

AVAILABLE BRUSHES

Nylon/Silicon Carbide (Typical Grit 80, 120, 240)
Fladder Style - Specify Grit (60-400)