



Now available in 25", 37", 52", 62", & 74"

## SUPERBRUSH 52 x 2 DOUBLE BRUSH

- Sealer-sand and whitewood sand doors in one pass at up to 60 ft/min. That is 3,600 2'x2' doors per hour. Works well for face frames and table tops too.
- 800 % faster than a 36" single head brush sander for doors.
- Conveyor, reinforced steel conveyor bed with a poly conveyor belt
- Sample testing available & encouraged
- Two, 2 HP motors, 208-230 Volt power, 3 Phase, TEFC, continuous-duty
- Bristle contact gauge (depth gauge) included, electronic & programmable
- Brush speed (RPM), variable 160 – 640 RPM
- Nylon & Flatter (60 – 400 grit) abrasive are just some of the brushes available
- Both brushes can be angled up to 15° for raised panel door sanding
- Straight-line metal up to 60 ft/min.
- Independently adjustable brush heads, RPM, contact, rotation
- 30 Amp, 3 Phase electrical service required
- Brush rotation is reversible (both brush heads).

|                                   |   |
|-----------------------------------|---|
| <b>Sanding Capacity</b>           |   |
| Maximum Width (in):               | 51  |
| Minimum Length (in):              | 24  |
| Maximum Thickness (in):           | 6 (varies with brush style)                                       |
| Minimum Thickness (in):           | 1/8   |
| <b>Dimensions (L x W x H/in):</b> |   |
| SuperBrush 52 x 2                 | 84 x 96 x 84  |
| Brush (in):                       | 11-12" diameter typical;<br>typical bristle length<br>1-1/2 to 3" |
| Brush Speed:                      | Infinitely variable<br>160 to 640 RPM                             |
| <b>Dust Hoods:</b>                |   |
| SuperBrush 52 x 2                 | 2 - 5" vacuum ports<br>1800 CFM. Min.                             |
| Height Adjustment (in):           | 1 HP motor<br>Electronically controlled                           |
| Conveyor Motor :                  | 2 HP<br>Infinitely variable 12-60<br>feet per minute              |
| Brush Motors (TEFC):              | (2) - 2 HP<br>208-230V, 60HZ;<br>continuous-duty.                 |
| Power Requirements:               | 3 Ph, 30 amp service  |
| Shipping Weight (lbs):            |   |
| SuperBrush 52 x 2                 | 7700  |

### 220 VOLT MODEL

**43552** SB Pro Series 36" Double Head Brush Sander -3 PH

### AVAILABLE BRUSHES

NYLON/SILCON CARBIDE (TYPICAL GRIT 80, 120, 240)  
FLADDER STYLE - SPECIFY GRIT (60-400)