



SUPERBRUSH 52 x 2 DOUBLE BRUSH

- Sealer-sand and whitewood sand doors in one pass at up to 60 ft/min. That is 3,600 2'x2' doors per hour. Works well for face frames and table tops too.
- 800 % faster than a 36" single head brush sander for doors.
- Conveyor, reinforced steel conveyor bed with a poly conveyor belt
- Sample testing available & encouraged
- Two, 2 HP motors, 208-230 Volt power, 3 Phase, TEFC, continuous-duty
- Bristle contact gauge (depth gauge) included, electronic & programmable
- Brush speed (RPM), variable 160 – 640 RPM
- Nylon & Flatter (60 – 400 grit) abrasive are just some of the brushes available
- Both brushes can be angled up to 15° for raised panel door sanding
- Straight-line metal up to 60 ft/min.
- Independently adjustable brush heads, RPM, contact, rotation
- 30 Amp, 3 Phase electrical service required
- Brush rotation is reversible (both brush heads).

Sanding Capacity	
Maximum Width (in):	51
Minimum Length (in):	24
Maximum Thickness (in):	6 (varies with brush style)
Minimum Thickness (in):	1/8
Dimensions (L x W x H/in):	
SuperBrush 52 x 2	84 x 96 x 84
Brush (in):	11-12" diameter typical; typical bristle length 1-1/2 to 3"
Brush Speed:	Infinitely variable 160 to 640 RPM
Dust Hoods:	
SuperBrush 52 x 2	2 - 5" vacuum ports 1800 CFM. Min.
Height Adjustment (in):	1 HP motor Electronically controlled
Conveyor Motor :	2 HP Infinitely variable 12-60 feet per minute
Brush Motors (TEFC):	(2) - 2 HP 208-230V, 60HZ; continuous-duty.
Power Requirements:	3 Ph, 30 amp service
Shipping Weight (lbs):	
SuperBrush 52 x 2	7700

220 VOLT MODEL

43552 SB Pro Series 36" Double Head Brush Sander -3 PH

AVAILABLE BRUSHES

NYLON/SILCON CARBIDE (TYPICAL GRIT 80, 120, 240)
FLADDER STYLE - SPECIFY GRIT (60-400)