



This product comes with a
2
Year Warranty



SUPERBRUSH 24", 36" AND OUR NEW 49" WIDTHS

- SuperBrush Applications include but are not limited to: white wood sanding, de-nibbing, sealer sanding, primer sanding, UV roughing, metal graining/straight lining, metal de-burring, sanding/polishing solid surface material, scuff sanding, shutter sanding, de-glossing and de-stressing
- Tension Rollers, 1-1/2" diameter, rubber covered, infeed and outfeed rollers, fully adjustable
- Conveyor, reinforced steel conveyor bed with a poly conveyor belt
- Sample testing available
- Continuous-duty 5 HP motor, 208-230 Volt power, single or 3 Phase
- Bristle contact gauge (depth gauge) included
- RPM Gauge displays brush speed, variable, 400 – 1200 RPM
- Wire, Nylon, Abrasive are just some of the brushes available
- Cast stand, zinc-plated steel bed, centerless ground column tubes
- Minimum of 600, 1200, or 1800 CFM dust collection recommended
- Ball bearings are sealed and permanently lubricated
- Electric height adjustment, high speed and adjustable speed (49" Brush Only)

220 VOLT MODELS

- 71267** SUPERBRUSH 24, 1 Ph, (one brush head included)
73267 SUPERBRUSH 24, 3 Ph, (one brush head included)
71367 SUPERBRUSH 36, 1 Ph, (one brush head included)
73367 SUPERBRUSH 36, 3 Ph, (one brush head included)
71497 SUPERBRUSH 49, 1 Ph, (one brush head included)
73497 SUPERBRUSH 49, 3 Ph, (one brush head included)

ACCESSORIES

- 98-0130** CASTERS (SET OF 4)
98-2501 25" INFEED/OUTFEED TABLES
98-3701 37" INFEED/OUTFEED TABLES
98-0118 PROSCALE™ DRO (DIGITAL DEPTH GAUGE)
98-0025 LOWRIDER LEGS WITH 4 CASTERS. LOWERS MACHINE 5-1/2"

AVAILABLE BRUSHES

- CARBON STEEL- OPEN AND DENSE WOUND WIRE
 SPRING STEEL- FINESSET WIRE
 NYLON/SILICON CARBIDE (TYPICAL GRIT- 80, 120, 240)
 FLADDER STYLE- SPECIFY GRIT (60-400)
 ADDITIONAL BRUSHES AVAILABLE

* SAMPLE TESTING ENCOURAGED

Sanding Capacity	
Maximum Width (in):	24, 36 or 49
Minimum Length (in):	10
Maximum Thickness (in):	11 (varies with brush style)
Minimum Thickness (in):	1/32
Dimensions (H x W x D/in):	
SuperBrush 24	52 x 46 x 35
SuperBrush 36	52 x 58 x 35
SuperBrush 49	50 x 71 x 31
Brush (in):	9-11 diameter typical; typical bristle length 1-1/2 to 3"
Brush Speed:	Infinitely variable 400 to 1200 RPM
Dust Hood:	
SuperBrush 24	Hinged back steel with 4" vacuum ports
SuperBrush 36	Hinged back steel with 2- 4" vacuum ports
SuperBrush 49	Hinged back steel with 3- 4" vacuum ports
Height Adjustment (in):	3/32 per turn, DepthGauge included
Conveyor Motor :	100 in.-lb. torque, direct drive D.C. motor, infinitely variable 0-15 feet per minute
Drive Motor (TEFC):	5 HP, 1740 RPM; 208-230V, 60HZ; continuous-duty.
Power Requirements:	1 Ph, 30 amp service 3 Ph, 20 amp service
Shipping Weight (lbs):	
SuperBrush 24	525
SuperBrush 36	605
SuperBrush 49	775