

DARE TO COMPARE

OPEN-END DRUM SANDERS



MODELS

FEATURES		JET 16-32	Delta 18-36	JET 22-44	Grizzly G0458	SUPERMAX 19-38
	Cast iron frame	NO	NO	YES	NO	YES
	Single alignment point to adjust conveyor parallel to drum	NO	NO	NO	NO	YES
	Indexed conveyor alignment (wide stock)	NO	NO	NO	NO	YES
	Extra wide conveyor for proper stock support	NO	NO	NO	NO	YES
	Shroud bolted directly to base to prevent pivoting	NO	NO	NO	NO	YES
	Thrust bearing design to eliminate backlash in the height adjustment	NO	NO	NO	NO	YES
	Extra space for easy access to abrasives	NO	NO	NO	NO	YES

MORE EXCEPTIONAL FEATURES!

- ◆ **INTELLISAND Technology:** Automatically adjusts conveyor speed based on load. Prevents gouging, damaging or burning stock.
- ◆ **Flatness Guarantee:** Precision flattened steel conveyor bed reinforced with four steel cross sections for no “flex” in conveyor, guaranteeing flatness to less than .010” across the width of the sander.
- ◆ **Steel—not plastic—** dust cover is formed to the shape of the drum to maximize air flow and dust extraction.
- ◆ **Tension rollers** are adjustable in height and hold down pressure, eliminating snipe.
- ◆ **Abrasive conveyor belt** offers the best grip for raw wood, giving you the ability to accommodate stock that is very short or thin.
- ◆ **Self-cooling drum** prevents overheating and extends abrasive life.
- ◆ **Award-winning!** *WOOD* magazine gave the 19-38 Drum Sander 5/5 Stars and *American Woodworker* gave it **Editor’s Pick!**



> Visit SuperMaxTools.com for full specs, videos, and dealer locations.

