




# SuperMax Tools

# DARE TO COMPARE OPEN-ENDED DRUM SANDERS

P. 888.454.3401  
F. 651.454.3465

SuperMaxTools.com  
sales@SuperMaxTools.com



								
	JET 16-32	SuperMax Tools 16-32	JET 18-36	SuperMax Tools 19-38	JET 22-44 Open Stand	JET 22-44 Closed Stand	Powermatic PM2244	SuperMax Tools 25-50
Stock #	723520K	71632	723530K	71938-D	649004K	649005K	1792244	72550
Drum Width	16"	16"	18"	19"	22"	22"	22"	25"
Maximum Sanding Width	32"	32"	36"	38"	44"	44"	44"	50"
Minimum Board Length	2-3/8"	2-1/4"	2-3/8"	2-1/4"	2-1/4"	2-1/4"	2-3/8"	2-1/4"
Minimum Sanding Thickness	1/32"	1/32"	1/32"	1/32"	1/32"	1/32"	1/32"	1/32"
Maximum Sanding Thickness	3"	3"	3"	4"	4"	4"	4	4"
Drive Motor	1.5HP, 115V, 14A, 1Ph	1.5HP, 110V, 15A, 1Ph	1.75HP, 115V, 15A, 1Ph	1.75HP, 110V, 15A, 1Ph	1.75HP, 115V, 15A, 1Ph	1.75HP, 115V, 15A, 1Ph	1.75HP, 115V, 14A, 1Ph	1.75HP, 110V, 15A, 1Ph
Recommended Circuit Size	20A	20A	20A	20A	20A	20A	20A	20A
Drum	1720 RPM	1740 RPM	1720 RPM	1740 RPM	1700 RPM	1700 RPM	1720 RPM	1740 RPM
Drum Diameter & Material	5" Aluminum	5" Aluminum & self-cooling	5" Aluminum	5" Aluminum & self-cooling	5" Aluminum	5" Aluminum	5" Aluminum	5" Aluminum & self-cooling
Conveyor Motor - Direct Drive, DC	43 In. Lbs. Tourque	43 In. Lbs. Tourque	43 In. Lbs. Tourque	43 In. Lbs. Tourque	43 In. Lbs. Tourque	43 In. Lbs. Tourque	1/30 HP	43 In. Lbs. Tourque
Conveyor Speed	0-10 FPM	0-10 FPM	0-10 FPM	0-10 FPM	0-10 FPM	0-10 FPM	0-10 FPM	0-10 FPM
Auto-adjusting conveyor speed	Sandsmart™	INTELLISAND™	Sandsmart™	INTELLISAND™	Sandsmart™	Sandsmart™	Feed Logic	INTELLISAND™
Flatness Guarantee		.010"		.010"				.010"
Machine Frame Material	Cast-Aluminum	Cast-Aluminum	Cast-Aluminum	Cast-Iron	Cast-Iron	Cast-Iron	Cast-Iron	Cast-Iron
Stand	Open Stand	Open Stand	Open Stand	Open Stand	Open Stand	Closed Stand w/ Casters	Closed Stand w/ Casters	Closed Stand w/ Casters
Dust Hood	Plastic with 1x4" Dust Port	Plastic with 1x4" Turbo Vented Dust Port	Plastic with 1x4" Dust Port	Metal - 1x4" Dust Port	Plastic with 1x4" Dust Port	Plastic with 1x4" Dust Port	Metal - 1x4" Dust Port	Metal - 1x4" Dust Port
Minimum Dust Collection Required	400 CFM	600 CFM	500 CFM	600 CFM	600 CFM	600 CFM	800 CFM	600 CFM
Quick Adjust Lever for fast height adjustment		YES						
Digital Read Out		YES (Built-in)		YES - Optional			YES (Built-in)	YES - Optional
Folding Infeed/Outfeed Tables for additional shop storage space (optional accessory)		YES - Optional		YES - Optional				YES - Optional
Single alignment point to adjust conveyor parallel to drum	YES	YES	YES	YES	YES	YES	YES	YES
Indexed conveyor alignment for wide stock		YES		YES				YES
Extra-wide stock support				YES			YES	YES
Thrust bearing design to eliminate backlash in height adjustment		YES		YES				YES
Extra space for easy access to abrasive fastening system		YES		YES				YES
Adjustable contact height on pressure rollers		YES		YES				YES
Adjustable hold-down pressure on pressure rollers		YES	YES	YES	YES	YES	YES	YES
Shipping Weight	156 lbs	158 lbs	190 lbs	286 lbs	296 lbs	345 lbs	418 lbs	369 lbs
Street Price	\$1,299.00	\$1,199.00	\$1,397.00	\$1,399.00	\$1,784.00	\$1,939.00	\$2,499.00	\$1,999.00
Infeed/Outfeed Tables	\$129.99		\$129.99	\$109.00	\$117.99	\$117.99	Included	\$109.00
Folding Infeed/Outfeed Tables	Not Available	\$119.00	Not Available	\$129.00	Not Available	Not Available	Not Available	\$129.00
Caster Set (4) #98-0130	\$133.99	\$89.00	\$133.99	\$89.00	\$133.99	Included	Included	Included