

## ShopPro 25 DRUM SANDER

## **EXCEPTIONAL** SUPERMAX FEATURES

INTELLISAND™ Technology: Automatically adjusts conveyor speed based on load

- Prevents gouging, damaging or burning stock
- Provides consistent finish even with varying grain pattern and density
- Greatly increases abrasive planing and dimensioning speed.
- Flatness guarantee

Precision-flattened steel conveyor bed reinforced with four steel cross sections for no "flex" in conveyor, guaranteeing flatness to less than .010 across the width of the sander.

- Abrasive conveyor belt offers the best grip for raw wood, giving you the ability to accommodate stock that is much shorter and thinner.
- Patented Abrasive Attachment System effectively tensions the abrasive wraps, preventing loosening, and overlapping.
- Easiest access to abrasive fastening system of any drum sander. Extra wide space to access fasteners to eliminate need for special tools.
- Self-cooling drum prevents overheating and extends abrasive life.



- Tension rollers are adjustable in height and hold down pressure, eliminating snipe.
- Cast stand, zinc-plate steel bed, centerless ground column tubes.

 Shipped assembled, no assembly required.



Maximum sanding width	25"
Minimum sanding length	2-1/4"
Maximum sanding thickness	4"
Minimum sanding thickness	1/32"
Dimensions	31" D x 46" W x 43" H
Drum	5" x 25" extruded aluminum
Dust hood	Steel hood with one 4" vacuum port, hinged at back (min. 600 CFM recommended)
Ball Bearings (1")	2, sealed and permanently lubricated
Conveyor motor	43 inlb. torque, direct drive D.C. motor, ranged variable 0-10 FPM
Drive motor (TECH)	1-3/4 HP
Power requirements	110-120V, 60Hz
Shipping weight	325 lbs

## #925002

## OPTIONAL ACCESSORIES

wraps

See page 20 for details.













#98-0118

Digital

depth gauge



READY-TO-CUT **BULK ABRASIVES** Aluminum oxyde and zirconium\* 24-120 grit (specify) See page 20 for details.